



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A61M 15/00, B05D 7/24, B65D 83/14	A1	(11) International Publication Number: WO 99/42154 (43) International Publication Date: 26 August 1999 (26.08.99)
---	-----------	---

(21) International Application Number: PCT/GB99/00532

(22) International Filing Date: 19 February 1999 (19.02.99)

(30) Priority Data:

9803780.7	23 February 1998 (23.02.98)	GB
9808804.0	24 April 1998 (24.04.98)	GB
9814717.6	7 July 1998 (07.07.98)	GB

(71) Applicant (for all designated States except US): **BESPAK PLC** [GB/GB]; Bergen Way, North Lynn Industrial Estate, Norfolk PE30 2JJ (GB).

(72) Inventor; and


(75) Inventor/Applicant (for US only): **WARBY, Richard, John** [GB/GB]; 93 Church Road, Emneth, Norfolk PE14 8AF (GB).(74) Agent: **BOULT WADE TENNANT**; 27 Fumival Street, London EC4A 1PQ (GB).

(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published*With international search report.*(54) Title: **DRUG DELIVERY DEVICES**

(57) Abstract

The invention relates to improvements in drug delivery devices and particularly those for dispensing a metered dose of medicament. Apparatus (10, 110) is provided for dispensing medicament wherein at least a portion of one or more of the internal surfaces of components of the apparatus (10, 110) which come into contact with the medicament during storage or dispensing has a layer of one or more cold plasma polymerised monomers bonded to a at least a portion thereof.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakistan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

DRUG DELIVERY DEVICES

This invention relates to improvements in drug delivery devices and particularly those for dispensing a metered dose of medicament.

In metered dose inhalers, an aerosol stream from a pressurised dispensing container is fired towards a patient or user of the inhaler into an air flow. The air flow is created by a user inhaling through a mouthpiece of the inhaler and the medicament is released into this air flow at a point between the air inlet holes and the mouthpiece.

Conventional metering valves for use with pressurised dispensing containers comprise a valve stem coaxially slidable within a valve member defining an annular metering chamber, and outer and inner annular seals operative between the respective outer and inner ends of the valve stem and the valve member to seal the metering chamber therebetween. The valve stem is hollow whereby in a non-dispensing position of the valve stem, the metering chamber is connected to the container and charged with product therefrom. The valve stem is movable against the action of a spring to a dispensing position wherein the metering chamber is isolated from the container and vented to atmosphere for the discharge of product.

Other drug delivery devices include apparatus in which capsules containing a powdered medicament are mechanically opened at a dispensing station where inhaled air subsequently entrains the powder, which is then dispensed through a mouthpiece.

A problem with all such drug delivery devices is that deposition of the medicament, or a solid component from a suspension of a particulate product in a liquid propellant, on the internal surfaces and

- 2 -

other components of the devices occurs after a number of operation cycles and/or storage. This can lead to reduced efficiency of operation of the device and of the resulting treatment in that deposition of the product reduces the amount of active drug available to be dispensed.

Some prior art devices rely on the dispenser being shaken in an attempt to dislodge the deposited particles as a result of the movement of a liquid propellant and product mixture. However, whilst this remedy is effective within the body of the container itself, it is not effective for particles deposited on the inner surfaces of the metering chamber. As the size of the chamber is significantly smaller, the restricted flow of fluid in the metering chamber (caused by the tortuosity of the flow path through the chamber) means that the fluid in the metering chamber does not move with enough energy to adequately remove the deposited particles.

One solution is proposed in our pending application GB 97211684.0 in which a liner of a material such as fluoropolymer, ceramic or glass is included to line a portion of the wall of a metering chamber in a metering valve. Although this solves the problem of deposition in these types of dispensers, it does require the re-design or modification of moldings and mould tools for producing the valve members to allow for the insertion of the liner.

It is an object of the present invention to provide drug delivery devices in general in which the deposition of the product and active drug component is minimised.

According to the invention there is provided apparatus for dispensing a medicament, wherein at least a portion of one or more of the internal

- 3 -

surfaces of components of the apparatus which come into contact with medicament during storage or dispensing has a layer of one or more cold plasma polymerised monomers bonded to at least a portion thereof.

A particular embodiment of the present invention will now be described, by way of example only, with reference to the accompanying drawings, in which:

Figure 1 is a cross-sectional view through an inhaler, which is one type of drug delivery device of the present invention; and

Figure 2 is a cross-sectional view of a metering valve used in another type of drug delivery device.

In Figure 1, an inhaler 10 for a product such as a medicament comprises a housing 11 for receiving a pressurised dispensing container 12 of a medicament and a mouthpiece 14 for insertion into the mouth of a user of the inhaler 10.

The container housing 11 is generally cylindrical and open at its upper end. A lower wall 15 of the housing 11 includes an annular socket 16 for receiving the tubular valve stem 17 of the container 12. The socket 16 communicates via a duct 18 ending in an orifice 19 with the mouthpiece 14. The lower wall 15 also has holes 20 for allowing air to flow through the container housing 11 into the mouthpiece 14.

The mouthpiece 14 may be generally circular or shaped to fit the mouth and is connected to or forms a part of the housing 11.

In use, a patient or user holds the inhaler 10, usually in one hand, and applies his mouth to the mouthpiece 14. The user then inhales through the

- 4 -

mouthpiece 14 and this creates an airflow through the cylindrical housing 11, from its open end around the dispensing container 12, through the holes 20 and into the mouthpiece 14. After the user has started
5 inhaling through the mouthpiece 14, the container 12 is depressed downwardly onto its stem 17 to release a dose of medicament from the container 12. The dose of medicament is projected by the pressure in the container 12 via the duct 18 and through the orifice
10 19. It then mixes with the airflow through the mouthpiece 14 and is hence inhaled by the user.

In traditional inhalers, all of the components are plastic mouldings, which gives rise to the deposition problems described above. The particular
15 problem areas in devices such as inhalers are the internal surfaces 21 of the mouthpiece 14, the internal surfaces 22 of the duct 18 and the walls 23 defining the orifice 19. In some inhalers 10, the diameter of at least a part of the duct 18 can be as
20 little as 0.5mm and so any deposition on its internal surfaces 22 could lead to not only the problem of a reduction in active drug components being available, but also dispensing difficulties.

The metering valve 110 illustrated in Figure 2 is
25 another type of drug delivery device or dispenser, and includes a valve stem 111 which protrudes from and is axially slidable within a valve member 112, the valve member 112 and valve stem 111 defining therebetween an annular metering chamber 113. The valve member 112 is
30 located within a valve body 114 which is positioned in a pressurised container (not shown) containing a product to be dispensed. The metering valve 110 is held in position with respect to the container by means of a ferrule 115 crimped to the top of the
35 container and sealing being provided between the valve

- 5 -

body 114 and container by an annular gasket 116.

An outer seal 117 and an inner seal 118 of an elastomeric material extend radially between the valve stem 111 and the valve member 112. The outer seal 117
5 is radially compressed between the valve member 112 and valve stem 111 so as to provide positive sealing contact, the compression being achieved by using a seal which provides an interference fit on the valve stem 111 and/or by the crimping of the ferrule 115
10 onto the pressurised container during assembly.

The valve stem 111 has an end 119 which protrudes from the valve member 112 and ferrule 115 which is a hollow tube and which is closed off by flange 120 which is located within the metering chamber 113. The
15 hollow end 119 of valve stem 111 includes a discharge port 121 extending radially through the side wall of the valve stem 111. The valve stem 111 further has an intermediate section 122, which is also hollow and defining a central passage and which has a pair of
20 spaced radial ports 123, 124 which are interconnected through a central cavity.

A spring 125 extends between a second flange 126, separating the intermediate section 122 of the valve stem 111 and an inner end 127 of the valve stem 111,
25 and an end of the valve body 114 to bias the valve stem 111 in a non-dispensing position in which the first flange 120 is held in sealing contact with the outer seal 117. The second flange 126 is located outside the valve member 112, but within the valve
30 body 114.

The metering chamber 113 is sealed from the atmosphere by the outer seal 117, and from the pressurised container to which the valve 110 is attached by the inner seal 118. In the illustration
35 of the valve 110 shown in Figure 1 radial ports 123,

- 6 -

124, together with the central cavity in the intermediate section 122 of the valve member 111 connect the metering chamber 113 with the container so that in this non-dispensing condition the metering member 113 will be charged with product to be dispensed.

Upon depression of the valve stem 111 relative to the valve member 112 so that it moves inwardly into the container, the radial port 124 is closed off as it passes through the inner seal 118, thereby isolating the metering chamber 113 from the contents of the pressurised container. Upon further movement of the valve stem 111 in the same direction to a dispensing position the discharge port 121 passes through the outer seal 117 into communication with the metering chamber 113. In this dispensing position the product in the metering chamber 113 is free to be discharged to the atmosphere via the discharge port 121 and the cavity in the hollow end 119 of the valve stem 111.

When the valve stem 111 is released, the biasing of the return spring 125 causes the valve stem 111 to return to its original position. As a result the metering chamber 113 becomes recharged in readiness for further dispensing operations.

The component parts of conventional drug dispensing devices, such as valve members, valve stems, inhaler housings and so on, are generally formed as single mouldings from material such as acetal, polyester or nylon which are prone to the deposition problems described above. Although in some cases it might be possible to include a separate liner of a material such as a fluoropolymer, ceramic or glass to line a portion of the area in which deposition problems occurs, this requires the redesign or modification of mouldings and mould tools so

- 7 -

that the components can accommodate such liners.

In the present invention we propose a solution in which the component parts of the drug dispensing devices are made by conventional tooling and moulds from the traditional materials listed above. They are then subjected to a cold plasma polymerisation treatment of one or more monomers which is a "hydrophobic" treatment which creates a very thin layer of the plasma polymer on the surface of the component parts which significantly reduces the deposition of active drugs on the relevant surfaces due to factors such as anti-frictional and waterproof characteristics and low surface energy.

The preferred monomers to use in this process are perfluoro-cyclohexane or perfluoro-hexane which would create a thin layer of plasma polymerised fluoro-cyclohexane or fluoro-hexane on the appropriate surface. Other fluorinated hydrocarbons may also be used, such as tetrafluoroethylene (TFE), trifluoroethylene, vinylidene fluoride and vinyl fluoride. The two monomers fluoroethylene and fluoropropylene may also be used to form the co-polymer fluorinated ethylene-propylene (FEP). As a further alternative, siloxanes may be used, such as dimethyl siloxane, to give a layer of plasma polymerised dimethylsiloxane.

The process is known as "cold plasma" treatment as the temperature within the body of the plasma is ambient. Thus thermoplastic materials such as polybutyrene terephthalate (PBT), nylon, acetile and tetrabutylene terephthalate (TBT) can be treated without fear of thermal damage. The treatment is a vacuum procedure in which the components are placed inside a chamber which is evacuated to less than 0.005 Torr. One or more monomers are introduced to the

- 8 -

chamber at a controlled rate and a 13.56 MHZ r.f. signal is applied to an external antenna. The plasma is ignited within the chamber and maintained for a given time at the preselected power setting. At the
5 end of the treatment the plasma is extinguished, the chamber flushed and the products retrieved. As a result a thin layer (for example 0.005 to 0.5 microns) of the plasma polymerised material is intimately bonded to the surface of the component.

10 Either an entire component within the drug delivery device, or just the surfaces of one or more component which would come into contact with the medicament during actuation, could be treated to provide an improved drug delivery device according to
15 the present invention. In the case of the type of inhalers as shown in Figure 1, surfaces 21, 22 and 23 may be treated. In a typical dry powder inhaler, the inner surface of the mouthpiece and any channel leading to the mouthpiece from the point of powder
20 storage, i.e. from a capsule, bulk storage chamber or a pre-metered chamber of a device. In the metering valve of Figure 2, the valve member 112 alone may be treated. However, additional benefits can be achieved in treating some or all of the other plastic and
25 rubber parts of the valve, including the valve body 114 and the seals 116, 117 and 118. Treatment of the seals 117 and 118 has the additional benefit that friction between the seals 117 and 118 and valve stem 111 is reduced resulting in easier operation of the
30 device. The level of friction between the valve stem 111 and seals 117 and 118 may be further reduced by treatment of the valve stem 111 itself. Such treatment reduces or eliminates the need for silicone emulsions or oils to be applied to the seals 117 and 118 and
35 valve stem 111. Treatment of the seals 116, 117 and

- 9 -

118 also has the benefits of reducing levels of extractibles where the seals are manufactured from elastomeric materials, reducing the permeability of the seals to the propellant in the pressurised dispensing container and reducing the levels of absorption of product onto the surfaces of the seals. The method can also be used to treat components of many other delivery devices including nasal pumps, non-pressurised actuators, foil storage types, breath actuated inhaler devices and breath co-ordinating devices and so on.

CLAIMS:-

1. Apparatus for dispensing a medicament wherein at least a portion of one or more of the internal
5 surfaces of components of the apparatus which come into contact with medicament during storage or dispensing has a layer of one or more cold plasma polymerised monomers bonded to at least a portion thereof.
10
2. Apparatus as claimed in claim 1 in which the layer is of a cold plasma polymerised fluorinated hydrocarbon.
- 15 3. Apparatus as claimed in claim 2 in which the one or more monomers for cold plasma polymerisation are selected from the group of materials comprising perfluoro-cyclohexane, perfluoro-hexane,
tetrafluoroethylene, trifluoroethylene, vinylidene
20 fluoride, vinylfluoride, fluoroethylene and fluoropropylene.
4. Apparatus as claimed in claim 1 in which the layer is of a cold plasma polymerised siloxane.
25
5. Apparatus as claimed in claim 4 in which the monomer for cold plasma polymerisation is dimethyl siloxane.
- 30 6. Apparatus as claimed in any one of the preceding claims in which the treated portion is made from a plastic polymer or synthetic rubber.

- 11 -

7. Apparatus as claimed in any one of the preceding claims in which the apparatus comprises a housing adapted to receive a container for storing the medicament, a mouthpiece and duct means connecting an outlet of the container with the mouthpiece, and at least a portion of one or more of the internal surfaces of the duct and/or mouthpiece is treated.

8. Apparatus as claimed in claim 7 in which at least a portion of the surfaces of the duct and the mouthpiece have a layer of plasma polymer bonded thereto.

9. Apparatus as claimed in any one of claims 1 to 6 in which the apparatus is a metering valve for use with a pressurised dispensing container, the valve comprising a valve stem co-axially slidable within a valve member, said valve member and valve stem defining an annular metering chamber, outer and inner annular seals operative between the respective outer and inner ends of the valve member and the valve stem to seal the annular metering chamber therebetween, wherein at least a portion of the metering valve is treated to have a layer of a plasma polymer bonded to at least a portion of an internal surface of the metering chamber.

10. Apparatus as claimed in claim 9 in which at least a portion of the surface of the valve member has the layer of plasma polymer bonded thereto.

11. Apparatus as claimed in claim 9 or claim 10 in which at least a portion of the surface of the valve stem has the layer of plasma polymer bonded thereto.

- 12 -

12. Apparatus as claimed in any one of claims 9 to 11 in which at least a portion of the surface of the seals have the layer of plasma polymer bonded thereto.
- 5 13. Apparatus as claimed in any one of claims 9 to 12 in which the valve further comprises a valve body in which the valve member is located, the valve body having the layer of plasma polymer bonded to at least a portion of its surface.
- 10 14. Apparatus as claimed in any one of claims 9 to 13 further comprising a gasket extending between the sealing surfaces of the metering valve and a pressurised dispensing container, said gasket having
- 15 the layer of plasma polymer bonded to at least a portion of the surface thereof.
- 20 15. Apparatus substantially as hereinbefore described with reference to and as shown in the accompanying drawings.

FIG. 1





FIG. 2



INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 99/00532

A. CLASSIFICATION OF SUBJECT MATTER

IPC 6 A61M15/00 B05D7/24 B65D83/14

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 A61M B05D B65D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 97 32672 A (POLAR MATERIALS INC) 12 September 1997	1-3,6
A	see page 5, line 4 - line 28	9,10,12, 14
X	WO 96 32345 A (ASHURST IAN C ;LI LI (US); HERMAN CRAIG S (US); RIEBE MICHAEL T (U) 17 October 1996 see page 9, line 6 - line 31	1-3
X	WO 97 47347 A (SARNOFF CORP) 18 December 1997 see page 7, line 4 - line 14	1-4,7,8
X	US 5 576 068 A (CABURET LAURENT ET AL) 19 November 1996 see abstract	1,4-6
	-/--	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

28 May 1999

Date of mailing of the international search report

07/06/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Villeneuve, J-M

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 99/00532

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 469 926 A (BOC GROUP INC) 5 February 1992 see page 3, line 34 - page 4, line 53 -----	1,4,6
A	US 4 252 848 A (DATTA PABITRA ET AL) 24 February 1981 -----	

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 99/00532

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9732672 A	12-09-1997	AU 2074097 A	22-09-1997
WO 9632345 A	17-10-1996	AU 5481296 A	30-10-1996
		BG 102023 A	31-07-1998
		BR 9604979 A	09-06-1998
		CA 2218179 A	17-10-1996
		CN 1186473 A	01-07-1998
		EP 0820414 A	28-01-1998
		HU 9800641 A	28-08-1998
		NO 974738 A	11-12-1997
		PL 322781 A	16-02-1998
		SK 139197 A	08-04-1998
WO 9747347 A	18-12-1997	US 5871010 A	16-02-1999
		US 5857456 A	12-01-1999
		AU 3388997 A	07-01-1998
		CA 2254928 A	18-12-1997
		EP 0917476 A	26-05-1999
		AU 3222597 A	07-01-1998
		CA 2255586 A	18-12-1997
		EP 0917475 A	26-05-1999
		WO 9747346 A	18-12-1997
US 5576068 A	19-11-1996	FR 2733758 A	08-11-1996
		EP 0823933 A	18-02-1998
		WO 9634926 A	07-11-1996
EP 0469926 A	05-02-1992	AU 655188 B	08-12-1994
		AU 8152191 A	06-02-1992
		CA 2048168 A	04-02-1992
		JP 6108255 A	19-04-1994
US 4252848 A	24-02-1981	NONE	